


Multi-conductor Cable



UL2547 Multi-Conductor Shielded Cable



Product Description

- Tinned, annealed, stranded or solid copper conductor.
- SR-PVC insulation
- Two to Three cores
- PVC jacket
- Tinned or bare copper wire, spiral shield
- Rated temperature: 80°C. Rated voltage: Not specified
- Pass UL VW-1&CSA FT1 vertical flame test

Applications

- For use in recording studios, sound systems and electronic circuits

Technical Data

UL Style& CSA Type	Cores	Conductor		Insulation Thickness	Nom. Dia	Spiral Shield	Jacket Thickness	Overall Diameter	Conductor Resistance at 20°C
		Gauge	No./OD						
		AWG	No./mm			No./mm			
UL2547CSA I A/B (Stranded)	2C	30	7/0.10	0.26	0.85	44/0.1	0.40	2.70	381.00
		28	7/0.127	0.26	0.90	46/0.1	0.40	2.80	239.00
		26	7/0.16	0.26	1.00	54/0.1	0.40	3.00	150.00
		24	11/0.16	0.26	1.15	62/0.1	0.40	3.30	94.20
		22	17/0.16	0.26	1.30	60/0.12	0.40	3.60	59.40
		20	21/0.178	0.26	1.50	72/0.12	0.40	4.00	36.70
		18	34/0.178	0.26	1.70	82/0.12	0.40	4.50	23.20
UL2547CSA I A/B (Stranded)	3C	16	26/0.25	0.26	2.10	98/0.12	0.40	5.10	14.60
		30	7/0.10	0.26	0.85	49/0.1	0.40	2.80	381.00
		28	7/0.127	0.26	0.90	53/0.1	0.40	3.00	239.00
		26	7/0.16	0.26	1.00	54/0.1	0.40	3.00	150.00
		24	11/0.16	0.26	1.15	69/0.1	0.40	3.50	94.20
		22	17/0.16	0.26	1.30	72/0.12	0.40	3.80	59.40
		20	21/0.178	0.26	1.50	82/0.12	0.40	4.20	36.70
		18	34/0.178	0.26	1.70	96/0.12	0.40	4.70	23.20
		16	26/0.25	0.26	2.10	114/0.12	0.40	5.40	14.60